

SPECIFICATIONS

Specifications are subject to change without notice. Specific warranty remedy limitations apply. Call 01929 459 459 for details.

TEMPERATURE*		GENERAL	
Temperature Range	-20 °C to +60 °C (-4 °F to +140 °F)	Reading Rate	1 reading every second up to 1 reading every 24 hours
Resolution	0.01 °C (0.018 °F)	Memory	32,256 readings
Calibrated Accuracy	±0.50 °C/± 0.9 °F (0 °C to +55 °C/32 °F to 131 °F)	LED Functionality	Green LED blinks every 5 seconds to indicate unit is logging Blue LED blinks every 15 seconds to indicate unit is in wireless mode Red LED blinks every 1 second to indicate alarm condition
Response Time	10 minutes free air	Wrap Around	Yes
WIRELESS		Start Modes	Immediate and delay start
RF Frequency	2.45 GHz IEEE 802.15.4 ultra-low power wireless transceiver with fully bi-directional communication	Calibration	Digital calibration through software
Band	ISM band 2.405-2.475 GHz	Calibration Date	Automatically recorded within device
Maximum Output Power	+0 dBm typical	Battery Type	9 V lithium or alkaline battery included; user replaceable with any 9 V battery
Receiver Sensitivity (RFC1000)	-95 dBm typical	Battery Life	4 years typical at 1 minute reading rate
Transmission Distance (to data loggers)	RFC1000, RFC1000-CE & RFC1000-IP69K 2,000 ft max. outdoors - line of sight unobstructed 500 ft max. indoors - typical urban environment	Data Format	For Display: °C or °F For Software: Date and time stamped °C, K, °F or °R
Transmission Distance (to other RFC1000's)	RFC1000 4,000 ft max. outdoors - line of sight unobstructed 1,000 ft max. indoors - typical urban environment RFC1000-CE 2,500 ft max. outdoors - line of sight unobstructed 700 ft max. indoors - typical urban environment RFC1000-IP69K 4,000 ft max. outdoors - line of sight unobstructed 1,000 ft max. indoors - typical urban environment	Time Accuracy	± 1 minute/month
		Computer Interface	USB to mini USB, 250,000 baud for standalone operation or RFC1000 required for wireless operation
		Operating System Compatibility	Windows XP SP3 or later
		Software Compatibility	Standard Software version 4.1.0.0 or later Secure Software version 4.1.3.0 or later
		Operating Environment	-20 °C to +60 °C (-4 °F to +140 °F), 0 %RH to 95 %RH non-condensing
		Dimensions	3.5 in x 3.25 in x 0.95 in (88.9 mm x 82.6 mm x 24.1 mm) Data logger only
		Material	ABS Plastic
		Weight	4.4 oz (125 g)
		Approvals	US (FCC), CA (IC), CE, South Korea (KCC), China (CMIIT), Japan (LCIE)
		Alarm	User configurable high and low audible, on-screen, email and text (SMS) alarms. Alarm Delay: A cumulative alarm delay may be set in which the device will activate the alarm (via LED) only when the device has recorded a user specified time duration of data.
		Audible Alarm Functionality	1 Beep per second for reading alarm above/below threshold

BATTERY WARNING: BATTERY MAY LEAK, FLAME OR EXPLODE IF DISASSEMBLED, SHORTED, CHARGED, CONNECTED TOGETHER, MIXED WITH USED OR OTHER BATTERIES, EXPOSED TO FIRE OR HIGH TEMPERATURE. DISCARD USED BATTERY PROMPTLY. KEEP OUT OF REACH OF CHILDREN.

Ordering Information

RFTemp2000A	PN 901442-00	Wireless Temperature data logger
RFC1000	PN 901383-00	Wireless RF receiver/repeater. USB to mini USB adapter & power supply included
RFC1000-CE	PN 901338-00	Wireless RF transceiver/repeater, CE approved for Europe. USB to mini USB adapter & power supply included
RFC1000-IP69K	PN 901389-00	Wireless RF transceiver/repeater, splash proof with an IP69K rating. USB to mini USB adapter included
RFC1000 Cloud Relay	PN 901900-00	MadgeTech Cloud Services Data Logging Hub
RFC1000-CE Cloud Relay	PN 901901-00	MadgeTech Cloud Services Data Logging Hub, CE approved for Europe
U9VL-J	PN 901804-00	Replacement battery for RFTemp2000A

For Quantity Discounts call 01929 459 459 or email sales@wpls.co.uk

Countries approved for use, purchase and distribution of the RFTemp2000A: Australia, Austria, Belgium, Bulgaria, Canada, Chile, China, Colombia, Croatia, Cyprus, Czech Republic, Denmark, Ecuador, Estonia, Finland, France, Germany, Greece, Honduras, Hungary, Iceland, Ireland, Israel, Japan, Latvia, Liechtenstein, Lithuania, Luxembourg, Malaysia, Malta, Mexico, New Zealand, Norway, Peru, Poland, Portugal, Romania, Saudi Arabia, Singapore, Slovakia, Slovenia, South Africa, South Korea, Spain, Sweden, Switzerland, Thailand, The Netherlands, Turkey, United Kingdom, United States, Venezuela, Vietnam

DOC 1260009-00 REV 6 2020.03.18