

Specifications

Specifications are subject to change without notice. Specific warranty remedy limitations apply. Call (603) 456-2011 or go to madgetech.com for details.

MEASUREMENT	
Input Connection	Removable screw terminal
Input Range	0 V to 30 V
Input Low	< 0.4 V
Input High	> 2.8 V
Internal Weak Pull-Up	< 60 μ A
Input Impedance	> 60 k Ω
Minimum Input Active (Low) Time	\geq 10 microseconds
Engineering Units	Native measurement units can be scaled to display measurement units of another type such as on/off, open/closed or rainfall.

GENERAL	
Start Modes	Immediate start Delay start up to 18 months Multiple pushbutton start/stop
Stop Modes	Manual through software Timed (specific date and time)
Multiple Start/Stop Mode	Start and stop the device multiple times without having to download data or communicate with a PC
Real Time Recording	May be used with PC to monitor and record data in real time
Password Protection	An optional password may be programmed into the device to restrict access to configuration options. Data may be read out without the password
Memory	465,578 readings; software configurable memory wrap
Wrap Around	Yes

LED Functionality	Green LED Blinks: 10 seconds to indicate logging and 15 seconds to indicate Delay or Manual Start Mode - Standby (waiting to start) Red LED Blinks: 10 seconds to indicate low battery and/or full memory
LEDs	2 status LEDs
Reading Rate	4 Hz up to 1 reading every 24 hours (Device will record 1 event per reading interval)
Calibration	Digital calibration through software
Calibration Date	Automatically recorded within device
Battery Type	3.6 V lithium battery included; user replaceable
Battery Life	10 years typical, dependent upon frequency and duty cycle
Data Format	State
Time Accuracy	\pm 1 minute/month at 25 °C (77 °F) (Stand alone mode)
Computer Interface	USB (interface cable required); 115,200 baud
Operating System Compatibility	Windows XP SP3 or later
Software Compatibility	Standard Software version 2.04.06 or later Secure Software version 4.1.6.0 or later
Operating Environment	-40 °C to +80 °C (-40 °F to +176 °F) 0 %RH to 95 %RH non-condensing
Dimensions	1.4 in x 2.1 in x 0.6 in (35 mm x 54 mm x 15 mm)
Weight	0.9 oz (24 g)
Material	Polycarbonate
Approvals	CE

BATTERY WARNING: Fire, explosion and severe burn hazard. Do not recharge, disassemble, heat above 100 °C (212 °F), incinerate, crush, or expose contents to water.





Solutions for High-tech Instrumentation
www.wessexpower.co.uk



E-commerce Instrumentation
www.loggershop.co.uk

Telephone +44(0)1929 459 459 Email sales@WPLS.co.uk

Ordering Information

Event101A	PN 900103-00	Event Data Logger
IFC200	PN 900298-00	USB interface cable
LTC-7PN	PN 900352-00	Replacement battery for the Event101A

For Quantity Discounts call (603) 456-2011 or email sales@madgetech.com